PRODUCT DATA SHEET

CGT-665C

GAFFERS TAPE - MATTE FINISH



DESCRIPTION:

A high quality, non-reflective, MATTE, vinyl coated cotton cloth tape with a strong rubber based adhesive, and wound on a 3" neutral core. Its low light reflectivity makes this product suitable for entertainment type applications where minimal visibility to no glare is required. Specially formulated adhesive allows for clean removal on most surfaces. Tape will conform well to irregular surfaces, and will not twist or curl during application. Excellent water and abrasion resistance. Tape is hand-tearable (cutting tools not required). Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED[®].

APPLICATIONS:

- Premium tape for use in the entertainment industry (concerts, tradeshows, etc.) for laying cable, wires, joining and building background props.
- Used on stage set-ups for marking placement (i.e. "spike" tape).
- Suitable as a book binding tape for seaming and edge reinforcement.
- Due to the printable surface of the tape, it is suitable for use as a "can" tape to mark film type contained within.

PHYSICAL PROPERTIES:

Backing

Vinyl Coated Cotton Cloth

Adhesive

Natural Rubber/Synthetic Resin Blend

Total Thickness

11.5 mils (0.292 mm)

Adhesion to Steel

50 oz/inch

, tarredien to oteo

42 lbs/inch

Tensile Strength Flame Spread

15

Smoke Developed

5

VOC Content

< 1 g/L

Temperature Resistance

40°F to 200°F

Available Colors (5)

Black, White, Gray, Red and Yellow

STORAGE: Tape should be stored in a cool, dry area at temperatures of 40°F to 90°F and 50% RH.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

(1607VH16300)