



DVT-76Y

DRY VINYL TAPE - YELLOW

DESCRIPTION:

DVT-76Y is a NON-ADHESIVE plasticized soft polyvinyl chloride (SPVC) film tape. The dry vinyl is wound on a 1.5" (38.1mm) neutral paper core.

FEATURES/BENEFITS:

- Easy unwinding characteristics – tape clings firmly to its own backing for tight wrap.
- High elongation and good strength to permit trouble-free binding of wiring harnesses for the automotive industry.
- Dry vinyl tape also used for plating applications – high stretch, good “cling” characteristics and great conformability provide for superior masking in hard chrome and other plating applications.

APPLICATIONS:

- Harness wire wrap
- Masking in plating applications
- Surface protection

PHYSICAL PROPERTIES:

Total Thickness	3.94 mils (0.10 mm)
Tensile Strength	8.6 lbs/inch
Elongation	200%
Dielectric Breakdown	6kV
Application Temperature	32°F to 120°F
Temperature Resistance	-13°F to 220°F
Specification/Certifications	UL510 Flame Resistant, Certificate Standard CE
Available Color (1)	Yellow

STORAGE:

Tape should be stored in a cool, dry area at temperatures of 70°F and 50% relative humidity.

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

(1606VHBEIJ02)